



Series 66 Thermostatic Water Controller

Unit No. 83007



ASSE 1017 Approved
ASSE Lead Free Certified*
 (Models 66-25, 66-50, 66-80 Lead Free Certified)

Certified to
CSA B125.3

Master water mixing valve shall be of the thermostatic type with liquid-filled motor. It shall have bronze body construction with replaceable corrosion-resistant components. Valve construction shall employ a sliding piston control mechanism. Piston and liner shall be of stainless steel material. Valve shall come equipped with union end stop and check inlets with removable stainless steel strainers.

Unit includes shut-off valve on tempered water outlet. Unit is assembled and tested with necessary fittings and nipples.

Valve No.	A N.P.T.	B N.P.T.	C
66-25*	3/4"	3/4"	10"
66-50*	3/4"	1"	10"
66-80*	1"	1 1/4"	11"
66-125	1 1/4"	1 1/2"	12 3/4"
66-150	1 1/2"	2"	13 1/4"
66-200	2"	2"	15"

FINISH

- Plain Bronze
- Chrome Plate
- Other

TEMP. RANGE

- 50° to 100° F
- 85° to 135° F
- 100° to 150° F

Special _____

SET POINT

- 80° F
- 110° F
- 130° F

Pressure Drop PSI	5	10	20	30	45	60	80
Valve Number	Capacity-GPM						
66-25*	9	12	17	21	25	28	32
66-50*	18	25	34	41	50	57	65
66-80*	28	39	54	66	80	91	103
66-125	43	60	85	103	125	144	165
66-150	52	72	100	124	150	174	193
66-200	64	96	133	165	200	230	265

Pressure Drop PSI	5	10	20	30	45	60	80
Valve Number	Capacity-LPM						
66-25*	34	45	64	79	94	106	121
66-50*	68	95	129	155	189	216	246
66-80*	106	148	204	250	303	344	390
66-125	163	227	322	390	473	545	624
66-150	197	273	379	469	568	659	731
66-200	242	363	503	625	757	871	1003



MANUFACTURING CO., INC.

5330 East 25th Street
 Indianapolis, Indiana 46218
 Phone (317) 261-1212
 Fax (317) 261-1208

Design and specification subject to change without notice.