



Series 4000 Exposed Thermostatic Mixing Valve

Unit No. 85003

Exposed mixing valve shall be of the thermostatic type with liquid-filled motor. It shall have bronze body construction with replaceable corrosion-resistant components. Valve construction shall employ a sliding piston control mechanism. Piston and liner shall be of stainless steel material. Piped and cabinet assemblies which have a down stream shut-off device shall include union end stop and check valves with removable strainer on each inlet.

Unit includes two tempered water outlets. The filler supply is equipped with a shut-off valve and vacuum breaker. The washout is equipped with a shut-off valve, vacuum breaker, washout hose and hose hook.

Unit is completely assembled as shown.

Units specified as polished chrome shall be polished chrome on all external surfaces.

FINISH: Bronze Valve $\frac{1}{2}$ "
 Polished Chrome $\frac{3}{4}$ "
 Other

DIMENSIONS:

A N.P.T.	B N.P.T.	C
$\frac{1}{2}$ "	$\frac{1}{2}$ "	8"
$\frac{3}{4}$ "	$\frac{3}{4}$ "	9 $\frac{1}{2}$ "

CAPACITIES - GPM SERIES 4000

Pressure Drop PSI	Capacity-GPM				
	5	10	20	30	45
Valve Size					
$\frac{1}{2}$ "	2.5	3.5	5.5	8.0	10
$\frac{3}{4}$ "	5.0	8.0	10.5	15	20

NOTE: Not normally supplied in a cabinet. If cabinet is required, contact factory for specifications.



MANUFACTURING CO., INC.

5330 East 25th Street
 Indianapolis, Indiana 46218
 Phone (317) 261-1212
 Fax (317) 261-1208

Design and specification subject to change without notice.